

CMCP312 Series 12 Channel DIN Rail Mount Switchable BNC Output



The CMCP-312 Provides a switchable BNC output for up to 12 Accelerometers. Providing easy access for connecting Data Collectors and Analyzers. The CMCP-312 small size allows it to be mounted almost anywhere convenience dictates. The CMCP-312 mounts on Standard 35 mm DIN Rail and Accelerometers are easily attached using the provided screw terminals. The CMCP-312 is for Interior Mounting, if mounted outdoors a suitable Junction Box should be used

Mounting:	DIN Rail (35mm)
Size:	2.07" Wide x 3.89" High x 3.0" Deep (52.5mm x 98,8mm x 79.2mm)
Terminals:	Screw Type Terminals with Pressure Plate
Wire Size:	22-14 AWG (Smaller Wire Uses Ferrules)
Flammability:	Enclosure UL94 V-O
Material:	Glass Filled Polycarbonate
Color:	Light Gray
Input:	Up to 12 Accelerometers
Output:	BNC

Ordering Information:

CMCP-312	12 Channel DIN Rail Mount Switchable BNC
----------	--

To Order Online Please Visit
www.stiwebstore.com

CMCP310 Series Switchable BNC Junction Boxes

The **CMCP310SS Stainless Steel** NEMA 4X enclosure is constructed from 14 gauge 304 Stainless Steel.

CMCP310SS	XXX	XX	Stainless Steel NEMA 4X	Dimensions
	06		6 Channels	9.5" x 7.0" x 4.0" (24.13 x 17.78 x 10.16 cm)
	12		12 Channels	9.5" x 7.0" x 4.0" (24.13 x 17.78 x 10.16 cm)
	24		24 Channels	15.5" x 13.0" x 6.0" (39.37 x 33.02 x 15.24cm)
	32		32 Channels	17.5" x 15.0" x 6.0" (44.45 x 38.10 x 15.24cm)
	48		48 Channels	17.5" x 15.0" x 6.0" (44.45 x 38.10 x 15.24cm)
		01	Internal BNC	
		02	External BNC	

CMCP261 Liquid Tight Strain Relief Connectors are used for either extension cable or multi-conductor wire entries into the CMCP310 BNC Junction boxes. Connectors are constructed of Polyamide and provide both environmental sealing and strain relief. The connectors are temperature rated to -40°F to +212°F (-60°C to +100°C) and have a pressure rating of up to 150 PSIG. Check your data sheet for the diameter of your extension cable.

CMCP261FG	XX	Min. O.D.	Max. O.D.
	01	0.08" (2)	0.20" (5)
	02	0.16" (4)	0.31" (8)
	03	0.20" (5)	0.35" (9)
	04	0.28" (7)	0.47" (12)
	05	0.35" (9)	0.70" (18)
	06	0.51" (13)	0.78" (20)

To Order Online Please Visit
www.stiwebstore.com