



Sales Technology Inc

Condition Monitoring Custom Products

CMCP205 Motor Fin Mounts

Features:

- Available in Four Sizes
- 416 SS (Magnetic)
- Kits Supplied with Adhesive, Dispenser, Mixing Nozzles
- Obtain Meaningful Vibration Data

Description:

The CMCP205 Motor Fin Mounts provide a mounting location for either magnetically mounted or permanently mounted accelerometers on motors where the bearing housing is not accessible. The Fin Mounts are machined from 416 SS and are adhesive mounted between the cooling fins of the motor. The CMCP205 Fin Mounts are provided in four sizes to accommodate a variety of motors and to keep the amount of required adhesive to a minimum. The CMCP205 can be purchased individually, and are available in kits in quantities of 50 or 100. Kits are supplied with adhesive and mixing nozzles.

Ordering Information:

CMCP205	-XX	-XX	Description
	01		1.25" x 0.50"
	02		2.00" x 0.50"
	03		1.75" x 0.25"
	04		1.00" x 0.25"
		50	Kit, Quantity of 50
		100	Kit, Quantity of 100

Optional:

CMCP206	Adhesive Filler
CMCP207	Dispenser
CMCP208	Mixing Nozzle



Specifications:

Material: 416 SS (Magnetic)
 Pad Thickness: 3/8"
 Pad Surface Finish: 32 μ in. RMS
 Pad Tap: 1/4-28

Your STI Sales Representative:

www.stiweb.com

Although care has been taken to assure the accuracy of the data compiled in this publication, Sales Technology, Inc. (STI) does not assume any liability for errors or omissions. STI reserves the right to alter any part of this publication without prior notice.

(5/3/01) Copyright © 1999-2001 by Sales Technology, Inc.

ALL RIGHTS RESERVED