



Sales Technology Inc

Condition Monitoring Custom Products

"Vibration Monitoring and Machine Protection Systems"

2911 S. Shore Blvd., Ste. 170, League City, TX 77573 Phone: 281.334.0766 Fax: 281.334.4255

Condition Monitoring Custom Products

CMCP512 Explosion Proof Loop Powered Display

Features

- **Explosion Proof**
- **Loop Powered**
- **Bright LED or LCD Display**
- **Class I, Division I**
- **Rugged NEMA 4X Enclosure**
- **Switch Selectable Range and Decimal Point, -1999 to 1999**
- **Loop Drop only 4.5 Volts (LED) 1.8 Volts (LCD)**



Description

The CMCP512 Explosion Proof Loop Powered Display is designed for applications where a simple inexpensive display is required. The CMCP512 gets its power from the 4-20mA input loop so there is no need for additional wiring or batteries. The CMCP512 is housed in a rugged NEMA 4X Explosion Proof Enclosure and can be mounted virtually anywhere.

In addition to the key features listed above, the CMCP512 offers users a adjustable display, it has a switch selectable range and decimal point.

Specifications

Power: 4-20mA Loop Powered
 Input Range: 4-20mA
 Display: 3 1/2 inch Digital LED or LCD
 Loop Drop: 4.5 Volts
 Operating Temperature: -20° C to +80° C
 Relative Humidity: 0-95%, non-condensing
 Dimensions: 4 1/2" W 6" H 6" D
 Mounting: 2 Bolt Mount (Standard)
 Approvals: FM, CSA, UL
 Class I (BCD), Class II (E,F,G) Class III

Ordering Information:

CMCP512	-XX	Description
	00	LED Display
	01	LCD Display

Although care has been taken to assure the accuracy of the data compiled in this publication, Sales Technology, Inc. (STI) does not assume any liability for errors or omissions. STI reserves the right to alter any part of this publication without prior notice.

(5/3/01) Copyright © 1999-2001 by Sales Technology, Inc.

ALL RIGHTS RESERVED

Your STI Sales Representative:

www.stiweb.com