




CMCP403 Series Cable Bulk Cable



Features:

- Bulk Cable for Field Installation
- Three Conductor, 20AWG Shielded Cable
- General Purpose TPR Cable (110°C)
- High Temperature FEP Cable (200°C)
- Overall Braided Shield with Interweaved Drain Wire
- UV, Oil and Chemical Resistant
- Circular Cross Section for Improved Sealing
- Flexible and Abrasion Resistant Jacket

Specifications

CMCP403L General Purpose Cable (Black Jacket)

AWG and Stranding:	20 AWG, 7 Strands, Class B, Annealed Tinned Copper
Conductors:	3 (White, Black, Red)
Drain:	24AWG 7 Strands Annealed Tinned Copper
Cable Shield:	38AWG Tinned Copper Braid
Jacket Material:	Black Thermoplastic Elastomer (TPE)
Overall Diameter:	0.187" (4.75mm)
Filler Material:	Fibrillated Polypropylene
Temperature Rating:	-76 to +230°F (-60 to +110°C)
Capacitance:	29.7 pF/ft
Inductance:	0.083 µH/ft
Conductance DCR:	0.01073 Ω/ft. @ 20°C
Maximum Operating Voltage:	300V
Approvals:	UL Approved, RoHS II and REACH Compliant Suitable for Class 1 Division II Installations Per NEC 501.10(B)
Standards:	UV and Oil Resistant
Maximum Continuous Length:	1,000' (30.5m) ±10%

CMCP403H High Temperature Cable (Red Jacket)

AWG and Stranding:	20 AWG, 7 Strands, Class B, Annealed Tinned Copper
Conductors:	3 (White, Black)
Drain:	24AWG 7 Strands Annealed Tinned Copper
Cable Shield:	38AWG Tinned Copper Braid
Jacket Material:	Yellow Fluorinated Ethylene Propylene (FEP)
Overall Diameter:	0.186" (4.72mm)
Filler Material:	Fiberglass
Temperature Rating:	-76 to +392°F (-60 to +200°C)
Capacitance:	26.6 pF/ft
Inductance:	0.083 µH/ft
Conductance DCR:	0.01073 Ω/ft. @ 20°C
Maximum Operating Voltage:	300V
Approvals:	UL Approved, RoHS II and REACH Compliant Suitable for Class 1 Division II Installations Per NEC 501.10(B)
Standards:	Flame Retardant UV and Oil Resistant
Maximum Continuous Length:	1,000' (30.5m) ±10%

Ordering Information:

CMCP403L-XXXX
CMCP403H-XXXX

Bulk General Purpose TPE Cable, 3 Conductor, Specify Length in Feet in Place of -XXXX
Bulk High Temperature FEP Cable, 3 Conductor, Specify Length in Feet in Place of -XXXX
Note: 1,000' Maximum Continuous Length