

CMCP535(A) Displacement Transmitter/Monitor



Transmitter Features:


- Displacement Output (mils/ μm)
- Velocity Input IEPE/Mechanical
- 5 Selectable Ranges
- 4-20mA Output
- Two Buffered Outputs
- Class 1 Division 2, Groups B-D
- CE Approved

Monitor Features:

- OK, Alert and Danger Alarms
- 5A @250VAC Relay Outputs
- Latching or Non-Latching Alarms
- Trip Multiply (2x or 3x)
- Selectable Time Delay
- API 670 Compliant

The **CMCP550 Displacement Transmitter** and **CMCP535A Displacement Monitor** are compatible with all industry standard IEPE and Mechanical Velocity Sensors. Each transmitter provides constant current power for the associated sensor and processes the signal through an integration circuit to determine the overall amplitude in terms of Displacement in either mils or microns (μm). A 4-20mA DC output proportional to one of the five user selectable ranges can then be sent to the plant's PLC, DCS, SCADA or other control system to allow operations and maintenance staff to view real time machinery health, set alarms and trigger machine shutdowns for scheduled preventative maintenance. An OK Fault Detection Circuit is provided with the 4-20mA output so hardware or power failures can be differentiated by the control system to prevent nuisance alarms and false readings. The CMCP535 can be ordered with the optional alarm module by using the CMCP535A prefix. The optional alarm module provides OK, Alert and Danger alarms along with associated relays, selectable time delays and adjustable set points for standalone API 670 compliant machine protection. A Timed OK Danger Defeat circuit is also provided to prevent unwanted false trips. Multiple transmitters and/or monitors can be combined into a single enclosure or cabinet to create a cost effective, multichannel machine protection system with solid state reliability.

Dimensions:



CMCP535(A) Displacement Transmitter/Monitor

Specifications:

Electrical Specifications:	CMCP535
Input:	100 mV/in/sec (3.937mv/mm/sec) IEPE Velocity Sensor (-100V) 500mV/in/sec (19.685mv/mm/sec) IEPE Velocity Sensor (-500V) Other Sensitivities Available On Request
Output:	4-20 mA DC Proportional to Displacement (600 Ohms max. resistive load)
Frequency Response @ -3db	2 to 2,000 Hz
Power:	+24 VDC 50 mA Nominal (100 mA with Alarm Module) Reverse Polarity and Transient Protected
Accuracy:	1% Full Scale
Selectable Ranges:	5.0, 10.0, 15.0, 20.0, 25.0 mils 127, 254, 381, 508, 635 µm
Signal Detection:	Peak to Peak
Sensor Power:	Internal 4.4 mA Constant Current Diode
OK Circuit:	Green LED (On = OK), Not OK = Off and 4-20 mA < 2.0 mA
Timed OK/Alarm/Danger Defeat:	30 Seconds on Power Up or Loss of OK
Buffered Outputs:	Active Buffer, BNC and Terminal
Optional Filters:	Optional Pluggable High Pass and Low Pass Filters
Case:	Isolated
Terminals:	Screw Type, 24 AWG min, 12 AWG max.
Environmental Specifications:	
Operating Temperature:	-20°C to +80°C (-4°F to +176°F).
Storage Temperature:	-40°C to +95°C (-40°F to +203°F)
Relative Humidity:	0 - 95% Non-Condensing
Mechanical Specifications:	
Mounting:	32 mm (G style) or 35 mm (T style) DIN Rail.
Dimensions:	0.99"W x 3.11"H x 3.81"D (25.27 x 78.99 x 96.67 mm) Transmitter 1.67"W x 3.11"H x 3.81"D (42.3 x 78.99 x 96.67 mm) Monitor
Weight:	0.21 lb./0.40 lb. w/Alarm Module (0.095kg/0.18kg)
Certifications:	CE, RoHS, CSA & UL Approved Class I Division II B-D

Optional Alarm Module (Monitor):	CMCP535A
Number of Alarms/Relays	3 – OK, Alert and Danger
Alarm Indication:	OK = Green LED, Alert = Yellow LED, Danger = Red LED
Relay Specification:	3 - Form C, SPDT, 5 Amp 30 VDC/250 VAC, Latching or Non-Latching
Alarm Time Delay:	Separately Selectable 0.1, 1.0, 3.0 6.0 10.0 Seconds
Trip Multiply Function:	Terminal for None, 2X or 3X Alarm Limit Trip Multiply
Reset Function:	Terminal for Remote Reset if Latching Alarms Selected
Bypass Function:	Hold Reset to Common
Display Output:	0-5 VDC Switch Selectable Current Value, Alert and Danger Setpoint

Ordering Information:

CMCP535	-XXXX	Displacement Transmitter
CMCP535A	-XXXX	Displacement Monitor
	-100V	100 mV/in/sec IEPE Velocity Input
	-500V	500 mV/in/sec IEPE Velocity Input
	-500EV	500 mV/in/sec Electro Mechanical Input
	-Specify	Specify Input (Mod Charge May Apply)



1010 East Main St. League City, TX 77573 Phone: 281-334-0766 Fax: 281-334-4255
www.stiweb.com / www.stiwebstore.com