

Vibration Monitoring and Machine Protection Systems

1010 East Main Street, League City, TX 77573 Phone:281.334.0766 Fax: 281.334.4255 www.stiweb.com / www.stiwebstore.com

CMCP640 Series

Low Cost Field Installable MIL Connectors



CMCP640-01

- 2 Socket MIL 10-SL
- Solder Contact
- Straight Exit
- Maximum Cable Diameter of 0.22"
- Includes Connector and Strain Relief



CMCP640-02

- 3 Socket MIL 10-SL
- Solder Contact
- Straight Exit
- Maximum Cable Diameter of 0.22"
- Includes Connector and Strain Relief



CMCP640-03

- 2 Socket MIL 10-SL
- Solder Contact
- Side Exit
- Maximum Cable Diameter of 0.22"
- Includes Connector and Strain Relief



CMCP640-04

- 3 Socket MIL 10-SL
- Solder Contact
- Side Exit
- Maximum Cable Diameter of 0.22"
- Includes Connector and Strain Relief

Common Specifications:

Military Specification: MIL-DTL-5015 Series

Type: Cable Plug Insert Arrangement: 10-SL Connection: Solder Coupling: Threaded

Body Material: Aluminum Allot with Cadmium Coating

Operating Temperature: -55 to 125°C