

CMCP602LST Series

General Purpose 2 Socket MS Connector Cable Assembly Push On Seal Tight Connector – Black TPE Jacket



Features:

- General Purpose Cable Assembly
- Rugged Design for Permanent Installations
- 2 Socket MS Connector, MIL-C 5015 Style
- IP68 Push On Seal Tight Connector
- Viton Boot for Superior Chemical Resistance
- Black TPE Jacketed Cable
- UV, Oil and Chemical Resistant Cable
- Suitable for Class 1 Division 1/2 Locations
- Braided Shield with Drain Wire
- 120°C Temperature Rating

Typical Applications

Mates with Sensors Featuring a 2 Pin MS Connector

Connector Specifications

Connector Type:	2 Socket MS 5015 MIL-C 5015 Style
Shield Isolation:	Case Isolated
IP Rating	IP68

Cable Specifications

Jacket Material:	TPE (Thermoplastic Elastomer)
Jacket Color:	Black
Insulation:	TPE (Thermoplastic Elastomer)
Conductors:	2 Plus Drain Wire
Wire AWG:	20AWG (0.52mm ²)
Drain Wire AWG:	24AWG (0.21mm ²)
Shielding:	Braided Shield
Cable Diameter:	0.19" (4.8mm)
Weight:	0.048 Lbs/Ft (1.48kg/m)
Temperature Range:	-67 to +248°F (-55 to +120°C)
Capacitance Per Foot (pF/ft):	30pF/ft (98.42pF/m)

Optional Armor Specifications


Material:	Stainless Steel
Type:	Braided Armor
Diameter	Braid = 0.23" (5.84mm)



Cable Shown with Stainless
Steel Braided Armor and Locking Collar Connector

Connector Pinout / Wire Color

Color Code: A = White
 B = Back



Ordering Information:

CMCP602LST	-XX	-XX	-XX	-XX	2 Socket MS Cable Assembly, Push On IP68
	-16				16' (5m) Long
	-32				32' (10m) Long
	-64				64' (20m) Long
	-Specify				Specify Cable Length in Feet
		-01			Standard Cable, No Armor
		-03			Cable with Overall Stainless Steel Braided Armor
			-01		Tinned Leads on Fly End (Terminal Block Connection)
			-02		Spade Lugs Installed on Leads (Screw Terminal Connection)
			-03		BNC Jack on Fly End
			-04		BNC Plug on Fly End
					ISOalted – Shield Not Connected at Sensor End (Standard)
			-NI		Non-Isolated – Shield Connected at Sensor End

Example Part Number:

CMCP602LST-16-01-01
2 Socket MS Cable Assembly
16' (5m) Long
Standard Cable, No Armor
Tinned Leads on Fly End

Similar Products:



CMCP603LST Series
3 Socket Push On



CMCP603L
3 Socket Locking Collar