

## CMCP605M Series M12 Eurostyle Cable Assemblies for 4 or 5 Pin Sensors

### Features:



- M12 with Molded Strain Relief
- IP68 Locking Collar Connector
- Straight or Side Exit Versions Available
- 5 Pin M12 Connector Mates with 4 and 5 Pin Sensors
- Twisted/Shielded Cable with Drain Wire
- General Purpose PUR Jacketed Cable
- Low Cost

### Typical Applications

Sensors with M12 4 or 5 Pin Connectors

### Connector Specifications:

Connector Type:	M12 (EuroFast)
Mates With:	4 or 5 Pin Male M12 Sensors
Material:	PUR
Contact Material:	Brass/Gold
Coupling Nut Material:	Stainless Steel

### Cable Specifications:


Jacket Material:	PUR
Jacket Color:	Yellow
Insulation:	Polypropylene
Conductors:	5 Plus Drain Shield
Wire AWG:	22AWG
Drain Wire AWG:	26AWG
Shielding:	Braided
Cable Diameter:	0.18" (4.5mm)
Weight:	0.028 Lbs/Ft
Temperature Range:	-40°C to +120°C (-40°F to +248°F)

### Environmental:

IP Rating:	IP68 Per IEC
------------	--------------


### Connector Pinout / Wire Color:

FEMALE END VIEW



1 =	Brown
2 =	White
3 =	Blue
4 =	Black
5 =	Grey

**Dimensions:**



**Ordering Information:**

<b>CMCP605M</b>	<b>-XX</b>	<b>-XX</b>	<b>-XX</b>	<b>M12 Cable Assembly for 4 and 5 Pin Sensors</b>
	-05			5 Meter Cable (16')
	-10			10 Meter Cable (32')
	-20			20 Meter Cable (64')
	-Specify			Specify Cable Length in Meters
		-01		Straight Exit Connector
		-02		Side Exit Connector