



CMCP667S-25P Series Coiled Cable Assemblies for the CMVA 10/55/60 Microlog Industrial Cable Connector Assembly



Features

- For SKF Microlog Data Collectors
- Connectors for All Sensor Types
- TPE Jacketed Coiled Cable
- Optional Safety Breakaway
- UV and Oil Resistant
- Three Cable Lengths (6', 10' and 15' Extended)
- -40 to +90 °C (-40 to +194 °F) Temperature Rating

Typical Application







Mates SKF Microlog CMVA 10/55/60/65 to specified connector types, for example Sensors featuring a 2 Pin MS Connector.



Coiled Cable Specifications

Jacket Material:	TPU (Thermoplastic Polyurethane)	
Jacket Color:	Blue	
Wire AWG:	22 AWG	(0.33 mm ²)
Cable Shield:	26 AWG	(0.13 mm ²) Alum-Polyester Foil
Cable Diameter:	0.23"	(5.7 mm)
Temperature Range:	-67 to +248 °F	(-55 to +120 °C)
Extended Length:	6, 10 and 15 feet	(1.8, 3.0 and 4.6 m)
Standards:	UV and Oil Resistant	

Connector Options

Connector Type	Order Code	Use	Image
ML 25 Pins	-25P	Input into Microlog	
2 Pin MIL Locking Collar	-2PLC	Accelerometer or Velocity Sensor with 2 Pin MS MIL Connectors	
2 Pin MIL Push-On Seal Tight	-2PLC	Accelerometer or Velocity Sensor with 2 Pin MS MIL Connectors	
BNC Plug	-MBNC	Universal BNC Connector, male	
BNC Jack	-FBNC	Universal BNC Connector, Female	
Safety Breakaway	-01	Optional Safety Disconnect Feature	

Ordering Information

Side A	Side B	Length	Breakaway	Option/Description
CMCP667S -25P				25 Pin connector for Microlog
	-2PLC			2 Pin MIL with Locking Collar
	-2PST			2 Pin MIL Push-On Seal Tight
	-MBNC			BNC Plug
	-FBNC			BNC Jack
		-06		6 Feet Extended (1.8m)
		-10		10 Feet Extended (3m)
		-15		15 Feet Extended (4.6m)
			-00	Without Safety Breakaway
			-01	With Safety Breakaway